

Calitate material S350GD + Z275. La cerere produsele se pot furniza și din alte tipuri de materiale.

TIP		Dimensiuni secționale					
		h (mm)	b ₁ (mm)	b ₂ (mm)	c ₁ /c ₂ (mm)	t _n (mm)	G (kg/m)
C100	C100-1.0	100	47	40	16	1	1.63
	C100-1.5	100	47	40	17.1	1.5	2.43
	C100-2.0	100	47	40	18.3	2	3.23
C120	C120-1.0	120	47	40	16	1	1.79
	C120-1.5	120	47	40	17.1	1.5	2.67
	C120-2.0	120	47	40	18.3	2.0	3.54
	C120-2.5	120	47	40	19.5	2.5	4.41
C150	C150-1.0	150	47	40	16.0	1.0	2.02
	C150-1.5	150	47	40	17.1	1.5	3.02
	C150-2.0	150	47	40	18.3	2.0	4.01
	C150-2.5	150	47	40	19.5	2.5	5.00
C180	C180-1.0	180	60	53	19.4	1.0	2.52
	C180-1.5	180	60	53	20.6	1.5	3.76
	C180-2.0	180	60	53	21.8	2.0	5.00
	C180-2.5	180	60	53	23.0	2.5	6.23
C200	C200-1.5	200	72	65	23.6	1.5	4.35
	C200-2.0	200	72	65	24.8	2.0	5.79
	C200-2.5	200	72	65	26.0	2.5	7.21
C250	C250-1.5	250	72	65	23.6	1.5	4.94
	C250-2.0	250	72	65	24.8	2.0	6.57
	C250-2.5	250	72	65	26.0	2.5	8.19
	C250-3.0	250	72	65	27.2	3.0	9.81
C300	C300-2.0	300	88	81	23.8	2.0	7.83
	C300-2.5	300	88	81	25.0	2.5	9.76
	C300-3.0	300	88	81	26.2	3.0	11.68
C350	C350-2.0	350	100	93	24.8	2.0	9.02
	C350-2.5	350	100	93	26.0	2.5	11.26
	C350-3.0	350	100	93	27.2	3.0	13.48
	C350-3.5	350	100	93	28.5	3.5	15.71
	C350-4.0	350	100	93	29.7	4.0	17.92
C400	C400-2.0	400	100	93	24.8	2.0	9.81
	C400-2.5	400	100	93	26.0	2.5	12.24
	C400-3.0	400	100	93	27.2	3.0	14.66
	C400-3.5	400	100	93	28.5	3.5	17.08
	C400-4.0	400	100	93	29.7	4.0	19.49

Calitate material S350GD + Z275. La cerere produsele se pot furniza și din alte tipuri de materiale.

TIP		Dimensiuni secționale				
		h (mm)	b ₁ (mm)	b ₂ (mm)	t _n (mm)	G (kg/m)
U100	U100-1.0	102	55	55	1.0	1.62
	U100-1.5	103	55	55	1.5	2.42
	U100-2.0	104	55	55	2.0	3.22
U120	U120-1.0	122	55	55	1.0	1.78
	U120-1.5	123	55	55	1.5	2.66
	U120-2.0	124	55	55	2.0	3.53
	U120-2.5	125	55	55	2.5	4.40
U150	U150-1.0	152	55	55	1.0	2.01
	U150-1.5	153	55	55	1.5	3.01
	U150-2.0	154	55	55	2.0	4.00
	U150-2.5	155	55	55	2.5	4.99
U180	U180-1.0	182	55	55	1.0	2.25
	U180-1.5	183	55	55	1.5	3.36
	U180-2.0	184	55	55	2.0	4.47
	U180-2.5	185	55	55	2.5	5.58
U200	U200-1.5	203	75	75	1.5	4.07
	U200-2.0	204	75	75	2.0	5.42
	U200-2.5	205	75	75	2.5	6.76
U250	U250-1.5	253	75	75	1.5	4.66
	U250-2.0	254	75	75	2.0	6.20
	U250-2.5	255	75	75	2.5	7.74
	U250-3.0	256	75	75	3.0	9.27
U300	U300-2.0	304	75	75	2.0	6.99
	U300-2.5	305	75	75	2.5	8.72
	U300-3.0	306	75	75	3.0	10.45
U350	U350-2.0	354	100	100	2.0	8.56
	U350-2.5	355	100	100	2.5	10.68
	U350-3.0	356	100	100	3.0	12.80
	U350-3.5	357	100	100	3.5	14.91
	U350-4.0	358	100	100	4.0	17.02
U400	U400-2.0	400	100	100	2.0	9.28
	U400-2.5	400	100	100	2.5	11.56
	U400-3.0	400	100	100	3.0	13.84
	U400-3.5	400	100	100	3.5	16.10
	U400-4.0	400	100	100	4.0	18.34

Calitate material S350GD + Z275. La cerere produsele se pot furniza și din alte tipuri de materiale.

TIP		Dimensiuni secționale					
		h (mm)	b ₁ (mm)	b ₂ (mm)	c ₁ /c ₂ (mm)	t _n (mm)	G (kg/m)
Z100	Z100-1.0	100	47	40	16	1	1.63
	Z100-1.5	100	47	40	17.1	1.5	2.43
	Z100-2.0	100	47	40	18.3	2	3.23
Z120	Z120-1.0	120	47	40	16	1	1.79
	Z120-1.5	120	47	40	17.1	1.5	2.67
	Z120-2.0	120	47	40	18.3	2.0	3.54
	Z120-2.5	120	47	40	19.5	2.5	4.41
Z150	Z150-1.0	150	47	40	16.0	1.0	2.02
	Z150-1.5	150	47	40	17.1	1.5	3.02
	Z150-2.0	150	47	40	18.3	2.0	4.01
	Z150-2.5	150	47	40	19.5	2.5	5.00
Z180	Z180-1.0	180	60	53	19.4	1.0	2.52
	Z180-1.5	180	60	53	20.6	1.5	3.76
	Z180-2.0	180	60	53	21.8	2.0	5.00
	Z180-2.5	180	60	53	23.0	2.5	6.23
Z200	Z200-1.5	200	72	65	23.6	1.5	4.35
	Z200-2.0	200	72	65	24.8	2.0	5.79
	Z200-2.5	200	72	65	26.0	2.5	7.21
Z250	Z250-1.5	250	72	65	23.6	1.5	4.94
	Z250-2.0	250	72	65	24.8	2.0	6.57
	Z250-2.5	250	72	65	26.0	2.5	8.19
	Z250-3.0	250	72	65	27.2	3.0	9.81
Z300	Z300-2.0	300	88	81	23.8	2.0	7.83
	Z300-2.5	300	88	81	25.0	2.5	9.76
	Z300-3.0	300	88	81	26.2	3.0	11.68
Z350	Z350-2.0	350	100	93	24.8	2.0	9.02
	Z350-2.5	350	100	93	26.0	2.5	11.26
	Z350-3.0	350	100	93	27.2	3.0	13.48
	Z350-3.5	350	100	93	28.5	3.5	15.71
	Z350-4.0	350	100	93	29.7	4.0	17.92
Z400	Z400-2.0	400	100	93	24.8	2.0	9.81
	Z400-2.5	400	100	93	26.0	2.5	12.24
	Z400-3.0	400	100	93	27.2	3.0	14.66
	Z400-3.5	400	100	93	28.5	3.5	17.08
	Z400-4.0	400	100	93	29.7	4.0	19.49

Calitate material S350GD + Z275. La cerere produsele se pot furniza și din alte tipuri de materiale.

TIP		Dimensiuni secționale							
		h (mm)	b ₁ (mm)	b ₂ (mm)	c ₁ /c ₂ (mm)	E (mm)	d ₁ /d ₂ (mm)	t _n (mm)	G (kg/m)
Σ200	Σ200-1.0	200	52	45	21	89.1	32	1.00	2.69
	Σ200-1.5	200	52	45	21	89.4	32	1.50	4.01
	Σ200-2.0	200	52	45	21	89.8	32	2.00	5.32
	Σ200-2.5	200	52	45	21	90.2	32	2.50	6.62
	Σ200-3.0	200	52	45	21	90.5	32	3.00	7.91
	Σ200-3.5	200	52	45	21	90.9	32	3.50	9.19
	Σ200-4.0	200	52	45	21	91.3	32	4.00	10.45
Σ250	Σ250-1.5	250	72	65	22.6	115.4	44	1.50	5.08
	Σ250-2.0	250	72	65	23.8	115.8	44	2.00	6.75
	Σ250-2.5	250	72	65	25	116.2	44	2.50	8.41
	Σ250-3.0	250	72	65	26.2	116.5	44	3.00	10.05
	Σ250-3.5	250	72	65	27	116.9	44	3.50	11.69
	Σ250-4.0	250	72	65	27	117.3	44	4.00	13.30
Σ300	Σ300-1.5	300	88	81	24	165.4	44	1.50	6.08
	Σ300-2.0	300	88	81	24.8	165.8	44	2.00	8.09
	Σ300-2.5	300	88	81	26	166.2	44	2.50	10.08
	Σ300-3.0	300	88	81	27.2	166.5	44	3.00	12.05
	Σ300-3.5	300	88	81	29	166.9	44	3.50	14.03
	Σ300-4.0	300	88	81	29.6	167.3	44	4.00	15.98
Σ350	Σ350-1.5	350	100	93	24	215.4	44	1.50	6.94
	Σ350-2.0	350	100	93	24.8	215.8	44	2.00	9.23
	Σ350-2.5	350	100	93	26	216.2	44	2.50	11.51
	Σ350-3.0	350	100	93	27.2	216.5	44	3.00	13.77
	Σ350-3.5	350	100	93	29	216.9	44	3.50	16.03
	Σ350-4.0	350	100	93	29.6	217.3	44	4.00	18.27
Σ400	Σ400-2.0	400	100	93	25	265.8	44	2.00	10.02
	Σ400-2.5	400	100	93	26	266.2	44	2.50	12.49
	Σ400-3.0	400	100	93	27	266.5	44	3.00	14.95
	Σ400-3.5	400	100	93	29	266.9	44	3.50	17.41
	Σ400-4.0	400	100	93	30	267.3	44	4.00	19.84